MSDS4417

MATERIAL SAFETY DATA SHEET

Product Name: Instant Cold Compress

Product Code: ICE1069 Page 1 of 9

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Instant Cold Compress

Product Code: ICE1069

Responsible Party: Basic Medical Industries, Inc.

12390 East End Ave Chino, California

91710

For further information contact MSDS Coordinator

8am - 6pm Pacific Time, Mon - Fri: 888-88-Basic (22742)

EMERGENCY OVERVIEW

Emergency Telephone Numbers:

888-88-Basic (22742) 909-548-4828

Health Hazards: Dry chemical of cold compress is an eye and skin irritant. Avoid contact with eyes, skin and clothing. Wash

thoroughly after handling.

Physical Hazards: Dry chemical is an oxidizer. Oxidizers can support combustion. Contact may increase flammability of other materials. Avoid contact with clothing and other combustible material.

Physical Form: Solid/Liquid <

Appearance: White solid in water bag <

Odor: None <

> NFPA HAZARD CLASS: Health: 1 (Slight)

> > Flammability: 0 (Least) Reactivity: 3 (High)
> > Other: OXY (Oxidizer)

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 2 of 9

2. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	% Weight	EXPOSURE GUIDELINE Limits Agency Type
Ammonium Nitrate CAS# 6484-52-2	40-70	Not Established
OTHER COMPONENTS	% Weight	EXPOSURE GUIDELINE Limits Agency Type
Water CAS# 7732-18-5	30-60	Not Established

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or you local agencies, for further information.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

Eye: Eye irritant. Contact may cause stinging, watering, redness, and swelling.

Skin: Skin irritant. Contact may cause redness, itching, burning and skin damage. No harmful effects from skin absorption have been reported.

Inhalation (Breathing): Low to moderate degree of toxicity by inhalation.

Ingestion (Swallowing): Low to moderate degree of toxicity by ingestion.

Signs and Symptoms: Effects of overexposure may include irritation of the nose, throat and digestive tract; coughing, nausea, vomiting, diarrhea, abdominal pain, breathing difficulties, and blood disorders (methemoglobinemia).

Cancer: No data available.

Target Organs: No data available.

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 3 of 9

Developmental: Inadequate data available for this material.

Other Comments: This material contains nitrate salts. Nitrates may be reduced by intestinal bacteria to nitrite. When absorbed, nitrites may result in effects on the blood (methemoglobinemia) and blood vessels (vasodilating and a fall in blood pressure). Symptoms of toxicity may include headache, fainting, fatigue, cyanosis, confusion, irregular heartbeats, and possible respiratory paralysis. Pre-existing heart disease may be aggravated by exposure to nitrates.

Pre-Existing Medical Conditions: Conditions aggravated by exposure may
 include heart, blood vessel and skin disorders.

4. FIRST AID MEASURES

Eye: Move victim away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek immediate medical attention. For direct contact, immediately hold eyelids apart and flush the affected eye(s) with clean water for at least 15 minutes. Seek medical attention.

Skin: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap or water. If irritation or redness develops, seek medical attention.

Inhalation (Breathing): If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion (Swallowing): If swallowed, seek emergency medical attention. If victim is drowsy or unconscious and vomiting, place on left side with the head down and do not give anything by mouth. If victim is conscious and alert and ingestion occurred within the last hour, vomiting should be induced for ingestion of large amounts (more than 5 ounces in an adult) under direction from a physician or poison center. If possible, do not leave victim unattended and observe closely for adequacy of breathing.

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 4 of 9

Note to Physicians: Nitrates in large doses may cause significant vasodilation and hypotension. Pre-existing ischemic heart disease may be aggravated by these effects. In large ingestions nitrates may cause methemoglobinemia. Methemoglobinemia should be suspected if cyanosis occurs. Methylene blue (1-2 mg/kg I.V. over several minutes) is an effective antidote for symptomatic methemoglobinemia.

5. FIRE FIGHTING MEASURES

Flammable Properties: Flash Point: None

OSHA Flammability Class: Not applicable

LEL/UEL: No data

Autoignition Temperature: No data

Unusual Fire & Explosion Hazards: Oxidizer. The dry chemical of this material is an oxidizer and may increase inflammability of any combustible substance. It is the nature of oxidizers to provide their own oxygen source; smothering a fire may be ineffective. Nitrate salts support combustion under certain conditions. Ammonium nitrate is capable of detonation if heated under confinement or if subjected to strong shocks. Organic or other easily oxidizable matter can sensitize it to a more readily explodable state. Do not allow product to evaporate to dryness, especially in contact with combustible materials.

Extinguishing Media: Use water only. Do not use dry chemical, carbon dioxide or foam.

Fire Fighting Instructions: For fires beyond the incipient stage, emergency responders in the immediate hazard area should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk. Water spray may be useful in minimizing or dispersing vapors. Cool equipment exposed to fire with water, if it can be done with minimal risk.

6. ACCIDENTAL RELEASE MEASURES

The dry chemical of this material is an oxidizer. Keep all sources of

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 5 of 9

ignition and hot metal surfaces away from spill/release. The use of explosion-proof equipment is recommended.

Stay upwind and away from spill/release. Notify person down wind of spill/release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section 8). Prevent spilled material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Dike far ahead of spill for later recovery or disposal. Spilled material may be absorbed into an appropriate absorbent material. Notify appropriate federal, state, and local agencies. Immediate cleanup of any spill is recommended.

HANDLING AND STORAGE

Handling: Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limits (see Section 2 and 8). Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Use good personal hygiene practice.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. Container should be disposed in an environmentally safe manner and in accordance with governmental regulations.

Before working on or in tanks which contain or have contained this material, refer to OSHA Regulations, ANSI Z49.1 and other governmental and industrial references pertaining to cleaning, welding, or other contemplated operations.

Storage: Use and store this material in cool, dry, well-ventilated areas away from heat and all sources of ignition. Post area "No Smoking or Open Flame." Solution is corrosive to copper, copper alloys, lead, and zinc. Store to avoid contact with incompatible materials such as ordinary combustibles, flammable liquids, greases, and those materials, including other oxidizers, that could react with the oxidizer or catalyze its decomposition (see Section 10). Prohibit accumulation of combustible waste in storage areas. Combustible construction materials that may be in contact with oxidizers shall be protected with a compatible coating to prevent impregnation of the combustible materials by

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 6 of 9

the oxidizers. Protect container(s) against physical damage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: If current ventilation practices are not adequate to minimize exposure, additional ventilation or exhaust systems may be required.

Personal Protective Equipment (PPE):

Respiratory: A NIOSH/MSHA approved air purifying respirator with a N95 filter may be used under conditions where airborne concentrations are expected to exceed exposure limits (see Section 2). Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin: The use of gloves impermeable to the specific material handled is advised to prevent skin contact, possible irritation, absorption, and skin damage (see glove manufacturer literature for information on permeability). Depending on conditions of use, apron and/or arm covers may be necessary.

Eye/Face: Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended. Depending on conditions of use, a face shield may be necessary.

Other Protective Equipment: A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm).

Flash Point: None

Flammable/Explosive Limits (%): LEL/UEL: No data

Autoignition Temperature: No data

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 7 of 9

Appearance: White solid in water bag

Physical State: solid/Liquid

Odor: None pH: No data

Vapor Pressure (mm Hq): No data

Boiling Point: No data

Freezing/Melting Point: No data

Solubility in Water: 100% Specific Gravity: approx 1.3

Evaporation Rate (nBuAc=1): No data

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of storage and handling. Dry chemical is an oxidizer and may promote combustion in other materials.

Conditions To Avoid: This material may be an oxidizer. Do not heat above 250°F. Do not let dry chemical or solution dry or crystallize in contact with organic, reactive, or combustible materials (see Sections 7).

Incompatible Materials: Avoid contact with reactive, combustible, or
 organic materials, such as wood, grain, organic chemicals, acids,
 corrosive liquids, sulfur, flammable liquids, chlorates,
 permanganates, finely divided materials, charcoal, coke, cork, or
 sawdust. Avoid contact with other oxidizers. Contact with
 alkaline materials may liberate ammonia.

Hazardous Decomposition Products: Material will not burn, but if involved in a fire, oxides of nitrogen may be generated. Exposure to heat may liberate ammonia fumes.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

No definitive information available on carcinogenicity, mutagenicity, target organs or developmental toxicity.

12. DISPOSAL CONSIDERATIONS

This material, if discarded as produced, may be a RCRA "characteristic" hazardous waste due to the characteristic(s) of ignitability (D001). If the material is spilled to soil or water, characteristic testing of

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 8 of 9

the contaminated materials is recommended. To assure proper disposal, consult with state and local regulations and disposal authorities.

13. TRANSPORT INFORMATION

Hazard Class or Division: Not classified as hazardous.

14. REGULATORY INFORMATION

This material contains the following chemicals subject to the reporting requirements of **SARA 313** and 40 CFR 372.

COMPONENT

CAS NUMBER

Ammonia (includes anhydrous 7446-41-7 ammonia and aqueous ammonia from water dissociable ammonium salts and other sources; 10 percent of total aqueous ammonia is reportable under this listing)

Water dissociable nitrate

None

compounds

Warning: This material contains the following chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5)

--None Known--

This material has not been identified as a carcinogen by NTP, IARC, or \mbox{OSHA} .

EPA (CERCLA) Reportable Quantity: --None--

15. DOCUMENTARY INFORMATION

Issue Date: 07/23/04
Previous Issue Date: None
Product Code: ICE1069

16. DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE

Issue Date: 07/23/04 Status: Final New

Product Code: ICE1069 Page 9 of 9

IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

Issue Date: 07/23/04 Status: Final New



BZK ANTISEPTIC TOWELETTE

Section I -- Product Identification

Product/Trade Name: BZK Antiseptic Towelette D 35100

Hazard Rating (NFPA): Health: 0

Flammability: 0 Reactivity: 0 Specific: None

Emergency or Information Phone No.: 914-365-1700 (M-F Daytime)

At other times, contact the local Poison Control Center

Chemical Name:

Section II -- Hazardous Ingredients Per 29 CFR 1910.1200

HAZARDOUS INGREDIENTS CAS NUMBER **ACGIH-TLV** None No components over 1% of formulation

Section III -- Physical/Chemical Characteristics

Color/Odor/Appearance: Applicator saturated with clear liquid

Boiling Point: N/A Flash Point: N/A Vapor Density: N/A Evaporation Rate: N/A Solubility in Water: Complete

Specific Gravity $(H_20=1)$:

Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used): N/A LEL: N/A UEL: N/A

Extinguishing Media: Any Special Firefighting Procedures: None Unusual Fire and Explosion Hazards: None

Section V -- Reactivity Data

Stability: Stable

Conditions to avoid: None known

Incompatibility: Anionic surfactants/soaps

Hazardous Decomposition of Byproducts: None

Polymerization: Will not occur

Section VI -- Health Hazard Data

Effects of Overexposure:

Skin: None

Eyes: May cause discomfort

Inhalation: None Ingestion: None Emergency and First Aid Procedures:

Skin Contact: Discontinue use if rash or irritation occurs. Eye Contact: Flush with cold water if splashed in eyes.

Inhalation: None
Ingestion: None
Target Organs: None

Section VII -- Spill and Disposal Procedure

Spill Control: Rinse into sewer system.

Waste Disposal Method: Follow local, state and federal regulations.

Handling and Storage: None

Section VIII -- Control Measures/Protection

Respiration: None
Ventilation: None
Protective Gloves: None

Eye Protection: If splash potential exists

Hygienic Practices: Good housekeeping practices should be followed.

Other: None

Section IX -- Transport/Shipping

DOT Shipping Name:

Technical Shipping Name:

DOT Shipping Classification: DOT not regulated

DOT ID Number:

DOT Label Requirements: UN/NA Number Regulations: Reportable Quantity:

Disclaimer:

The information furnished herein is believed to be accurate and represents the best data currently available to us. No warrant or implied, is made and Dynarex Corporation assumes no legal responsibility or liability resulting from its use.



Executive Headquarters: 10 Glenshaw Street, Orangeburg, NY 10962 Phone: (845) 365-8200 • Toll Free: (888) 335-7500 • (888) DYNAREX Fax: (845) 365-8201 • Email: sales@dynarex.com • www.dynarex.com

James Alexander Corporation 845 Route 94 Blairstown, NJ 07825 **Product Name: AMMONIA INHALANT SOLUTION**

MSDS Effective Date: September 10, 2004

Page 1 of 4

CHEMTREC 24 Hour Emergency Phone: (800) 424-9300 Note: The CHEMTREC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to JAC at (908) 362-9266.

-----I. PRODUCT IDENTIFICATION ------

Manufacturer's Name: James Alexander Corporation

Phone: (908)362-9266

Emergency Telephone No.: (800)424-9300 (CHEMTREC)

Address: 845 Route 94 Blairstown, NJ 07825

Product Name: AMMONIA INHALANT SOLUTION

Synonyms: N/A

D.O.T. Shipping Name: Air shipments: Flammable Liquid Corrosive NOS, 3- UN 2924, PGII

(Ammonia, ethanol)

Ground shipments: Consumer Commodity- ORM-D

NFPA Ratings: Health - 3 Flammability - 3 Instability - 1

------II. HAZARDOUS INGREDIENTS ------

-----OSHA----------ACGIH-----TLV/TWA CAS No. Component PEL/TWA TLV/STEL Ammonia 7664-41-7 50 ppm 25 ppm 35 ppm 1000 ppm Ethyl Alcohol 64-17-5 37.5 1000 ppm Not listed

------III. PHYSICAL DATA -----

Boiling Point: N/A for mixtures Melting Point: Unknown

Specific Gravity: 0.891 25/25 Vapor Pressure: Unknown

Vapor Density: Unknown Solubility in water: Very soluble

% volatiles by vol.: 55% **Evaporation Rate** (Butyl acetate=1): Unknown

Appearance and odor: Clear, pink to light red liquid. Pungent odor of ammonia.

pH: Unknown

-----<u>IV FIRE & EXPLOSION INFORMATION</u> ------

Flash Point: Less than 50 degrees F Test Method: Pensky Martens Closed Cup **Autoignition temp**: Ammonia 1204 degrees F (651°C); Ethyl Alcohol: 685 degrees F (363°C)

Flammable limits in air % by volume: Lower (Unknown) Upper(Unknown)

Extinguishing media: "Alcohol resistant" foam, CO₂ or dry chemical.

James Alexander Corporation 845 Route 94 Blairstown, NJ 07825 Product Name: AMMONIA INHALANT SOLUTION

MSDS Effective Date: September 10, 2004

Page 2 of 4

CHEMTREC 24 Hour Emergency Phone: (800) 424-9300 Note: The CHEMTREC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to JAC at (908) 362-9266.

Special fire fighting procedures:

NOTE: Individuals should perform only those fire-fighting procedures for which they have been trained.

Remove all sources of ignition. Move exposed containers from fire area if it can be done without risk. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece operated in positive pressure mode. Spray extinguishing media directly into base of flames. Water may be used to keep fire-exposed containers cool.

Unusual fire and explosion hazard: When heated, mixture will give off ammonia gas, a strong irritant to eyes, respiratory tract, and mucous membranes. Other toxic gases produced are oxides of nitrogen, carbon monoxide, carbon dioxide and hydrogen. Closed containers exposed to heat may develop pressure and explode.

Alcohol vapors are heavier than air and may travel a considerable distance to a source of ignition and flash back. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

------V. HEALTH HAZARD INFORMATION ------

Primary routes of exposure: Inhalation, eye contact, skin contact, ingestion.

Signs and symptoms of overexposure:

<u>Inhalation</u>: Irritation or burns of the respiratory system, headache, coughing, lung congestion or inflammation, pulmonary edema, breathing difficulty. Headache, dizziness, drowsiness, loss of appetite and an inability to concentrate.

Eve contact: Severe irritation or burns, may lead to blindness.

Skin contact: Local irritation, dry skin, burns.

<u>Ingestion</u>: Burning pain in mouth, throat, constriction of throat, coughing, followed by nausea, vomiting or diarrhea. Ingestion may prove fatal.

Medical Conditions Aggravated by Exposure: Individuals with pre-existing nervous system disorders, skin disorders, eye problems, or impaired respiratory function may be more susceptible to the effects of overexposure.

-----<u>VI. EMERGENCY AND FIRST AID PROCEDURES</u> ------

For Inhalation: Remove subject immediately to fresh air. Give artificial respiration if victim is not breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

James Alexander Corporation 845 Route 94 Blairstown, NJ 07825 Product Name: AMMONIA INHALANT SOLUTION

MSDS Effective Date: September 10, 2004

Page 3 of 4

CHEMTREC 24 Hour Emergency Phone: (800) 424-9300 <u>Note</u>: The CHEMTREC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to JAC at (908) 362-9266.

For Eye Contact: Immediately flush eyes with copious amounts of water for at least 15 minutes. Eyelids should be held apart and away from eyeball for thorough rinsing. Do not permit victim to rub eyes. Get immediate medical attention.

For Skin Contact: Immediately flush skin with copious amounts of water for at least 15 minutes while removing contaminated clothing and shoes. Do not rub or apply ointment to affected area. Obtain medical attention if irritation persists. Wash clothing before re-use.

For Ingestion: Contact a Poison Control Center *immediately*. Do NOT induce vomiting. If conscious, have victim swallow large amounts of water. Do not give anything by mouth to an unconscious or convulsing person. Get *immediate* medical attention.

-----<u>VII. TOXICITY DATA</u> -----

None of the components present in this formulation are currently classified as carcinogens in the NTP Annual Report on Carcinogens, IARC Monographs or by OSHA.

-----VIII. PERSONAL PROTECTION -----

Storage Requirements: Protect containers from physical damage. Detached or outside storage is preferred. Inside storage should be in an NFPA approved flammable liquids storage room or cabinet. Store in corrosion-proof area at temperatures below 77 degrees F (25°C). Do not store in direct sunlight. Isolate from incompatible materials. Keep containers tightly closed.

<u>Handling Requirements</u>: All ignition sources should be eliminated. Remove closure carefully; internal pressure may be present. Keep closure up to prevent leakage. When contents are being transferred, metallic containers must be bonded to the receiving container and grounded to avoid static discharges. Never use pressure to empty containers. Replace closure carefully after each opening.

<u>Ventilation:</u> Not required for product (JAC unit dose inhalant) use. When handling bulk material, use general or local exhaust ventilation to meet TLV requirements. Where engineering controls are not feasible or sufficient to achieve full conformance with acceptable exposure limits, use NIOSH approved respiratory protection equipment. Care must be taken to assure that any respirator chosen is capable of protecting the user from **both ammonia and ethyl alcohol vapors**. In some cases, a self-contained breathing apparatus may be advisable.

Eve Protection: Not required for product (JAC unit dose inhalant) use. When handling bulk material, always wear gas-tight, splash-proof chemical safety goggles meeting OSHA 29CFR 1910.133 specifications.

Skin Protection: Not required for product (JAC unit dose inhalant) use. Use rubber gloves, protective suit, face shield and overshoes when handling bulk product.

James Alexander Corporation 845 Route 94 Blairstown, NJ 07825 Product Name: AMMONIA INHALANT SOLUTION

MSDS Effective Date: September 10, 2004 Page 4 of 4

CHEMTREC 24 Hour Emergency Phone: (800) 424-9300 Note: The CHEMTREC emergency number is to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to JAC at (908) 362-9266.

-----IX. HAZARDOUS REACTIVITY -----

Stable at room temperature. Hazardous polymerization will not occur. However, product will react exothermically with acids. Releases ammonia vapor when heated. Ammonia component will decompose to hydrogen and oxides of nitrogen when heated. Carbon monoxide gas may also be produced when heated.

<u>Conditions To Avoid:</u> Sunlight, heat (heating above ambient temperatures causes the vapor pressure of the solution to increase).

Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

-----X SPILL, LEAK AND DISPOSAL PROCEDURES ------

For large spills, stop leak if you can do so without risk. Extinguish all sources of ignition. Wear self-contained breathing apparatus, chemical safety goggles and full protective clothing. Ventilate area. Spilled liquids should be contained and not washed into sewers or ground water. Contain by diking with non-combustible absorbent materials and place residue in DOT approved waste container.

Comply with all applicable local, state and federal regulations on spill reporting, handling and disposal of waste.

Other Precautions: Containers, even those that have been emptied, will retain product residue and vapors. Handle empty containers as if they were full.

Prepared By: David Robinson

Title: Vice President

Date of Initial Preparation: June 1989 **Latest Revision Date:** September 10, 2004

NOTE: This Material Safety Data Sheet is intended only as a guide to the appropriate precautionary handling of the material by a person trained in, or supervised by a person trained in, the safe handling of chemical materials. James Alexander Corporation (JAC), expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose with respect to the product or information provided herein.

All information appearing herein is based upon data obtained from the manufacturer(s) and/or recognized technical sources. While the information is believed to be accurate, JAC makes no representations as to its accuracy or sufficiency. Conditions of use are beyond JAC's control and therefore, users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other material or in any other process.

MSDS Material Safety Data Sheet Blistex Inc.



Blistex Foille Ointment

MSDS Number: 025-9302 Revision Date: 11/10/04

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Blistex Inc. 1800 Swift Drive

Oak Brook, IL 60523

Contact: Director of Quality Systems **Telephone Number:** (630) 571-2870

FAX Number: E-Mail: Web

Product Name: Blistex Foille Ointment

Revision Date: 11/10/04 **MSDS Number**: 025-9302

2

COMPOSITION/INFORMATION ON INGREDIENTS


3 HAZARDS IDENTIFICATION

Route of Entry: Skin, Ingestion, Mucus membranes

Target Organs: N/A **Inhalation:** No

Skin Contact: Mild allergic conditions in and around the lip area may occur. Irritation and swelling may develop.

Eye Contact: Irritation Ingestion: N/A



MSDS Material Safety Data Sheet Blistex Inc.



Blistex Foille Ointment

MSDS Number: 025-9302 Revision Date: 11/10/04

4 FIRST AID MEASURES

Inhalation: N/A

Skin Contact: Wash with luke warm water and mild soap.

If irritation or rash develops, stop use. If condition does not improve in several days, seek medical

assistance.

Eye Contact: Flush with luke warm water for 15 minutes.

Ingestion: If discomfort or concerns arise, contact a physician or Poison Control Center.

5 FIRE FIGHTING MEASURES

Flash Point: < 545 F
Flash Point Method: Open Cup
Burning Rate: Unknown
Autoignition Temperature: Unknown
LEL: Unknown
Unknown
Unknown

CO2, Dry Chemical, Foam

6 ACCIDENTAL RELEASE MEASURES

Use inert absorbent material to collect spilled product. Collect and place in drums for disposal.

Dispose of according to local, state and federal regulations.

HANDLING AND STORAGE

Handling Precautions: Keep in closed containers when in bulk form.

Storage Requirements: Store at room temperature.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: N/A

Protective Equipment: Use NIOSH approved gloves and goggles when handling in raw, bulk form.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Homogeneous Ointment - Greenish-yellow/green cast

Physical State:CreamyBoiling Point:N/AOdor:CharacteristicFreezing/Melting Pt.:N/A

pH: 6.0 - 8.2 Solubility: Insoluble in water Vapor Pressure: N/A Spec Grav./Density: 0.910 - 0.930

Vapor Density: N/A

MSDS Material Safety Data Sheet Blistex Inc.



Blistex Foille Ointment

MSDS Number: 025-9302 Revision Date: 11/10/04

10 STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: Intense heat - Freezing

Materials to avoid (incompatability): Oxidizing agents

Hazardous Decomposition products: None Hazardous Polymerization: None

11 TOXICOLOGICAL INFORMATION

Unknown

12 ECOLOGICAL INFORMATION

Unknown

13 DISPOSAL CONSIDERATIONS

Follow local, state and federal regulations.

14 TRANSPORT INFORMATION

15 REGULATORY INFORMATION

Active ingredients approved by FDA as safe and effective.

16 OTHER INFORMATION

END OF MSDS DOCUMENT