

Issuing Date 03-Apr-2007

Revision Date 11-Mar-2011

Revision Number 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Mothers Mag & Aluminum Polish
Product Code(s) 05100, 05101, 05102, 05104
Recommended Use Metal polish

Supplier Address

MOTHERS POLISHES WAXES
CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

WARNING!

Emergency Overview

May be harmful if swallowed
Harmful: may cause lung damage if swallowed
May cause skin and eye irritation
Repeated contact may cause allergic reactions in very susceptible persons
May cause drowsiness and dizziness
Combustible material

Appearance White

Physical State Solid.

Odor Pine

Potential Health Effects

Principle Routes of Exposure Skin contact. Eye contact.

Acute Toxicity

Eyes
Skin

May cause irritation.

May cause skin irritation and/or dermatitis. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking.

Inhalation

May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Ingestion

Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause additional affects as listed under "Inhalation". Harmful: may cause lung damage if swallowed.

Chronic Effects

Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

Aggravated Medical Conditions

Allergies. Skin disorders. Respiratory disorders. Central nervous system. Pre-existing eye disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects. Irritants. Sensitizers. Epoxies.

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Petroleum distillates, hydrotreated light	64742-47-8	25-50
Alumina	1344-28-1	25-50
Stearic acid	57-11-4	<10
Triethanolamine	102-71-6	<10
Tall oil fatty acids	61790-12-3	<10
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-	9036-19-5	<10
Hexylene glycol	107-41-5	<10

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Consult a physician.
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Combustible material: may burn but does not ignite readily.
Flash Point	194°F / 90°C
Suitable Extinguishing Media	Carbon dioxide (CO ₂). Dry powder. Dry chemical. Foam.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.
Explosion Data	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	Yes.
Specific Hazards Arising from the Chemical	Thermal decomposition can lead to release of irritating gases and vapors.
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
NFPA	Health Hazard 1 Flammability 2 Instability 0 Physical and Chemical Hazards N/A
HMIS	Health Hazard 1 Flammability 2 Physical Hazard 0 Personal Protection B

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Avoid contact with the skin and the eyes.
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8.
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material. Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains.

7. HANDLING AND STORAGE

Handling	Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. Avoid contact with skin and eyes.
Storage	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist)	TWA: 5 mg/m ³ (as oil mist)	
Hexylene glycol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m ³	Ceiling: 125 mg/m ³ Ceiling: 25 ppm
Alumina 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	
Triethanolamine 102-71-6	TWA: 5 mg/m ³		
Tall oil fatty acids 61790-12-3	5 mg/m ³ (resp) 10 mg/m ³ STEL (resp)	5 mg/m ³ (resp)	

Immediately Dangerous to Life or Health.

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
Engineering Measures	Showers Eyewash stations Ventilation systems
Personal Protective Equipment	
Eye/Face Protection	Safety glasses with side-shields.
Skin and Body Protection	Protective gloves.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White.	Odor	Pine.
Odor Threshold	No information available.	Physical State	Solid
pH	No information available.		
Flash Point	194°F / 90°C	Autoignition Temperature	No information available.
Decomposition Temperature	No information available.	Boiling Point/Boiling Range	No information available
Melting Point/Range	55°C		
Flammability Limits in Air	No information available.	Explosion Limits	No information available.
Solubility	No information available	Evaporation Rate	No information available
Vapor Pressure	No data available	Vapor Density	No data available
VOC Content (%)	<30		

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Incompatible Products	None known based on information supplied.
Conditions to Avoid	Heat, flames and sparks.
Hazardous Decomposition Products	None under normal use. Thermal decomposition can lead to release of irritating gases and vapors.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

Inhalation	May cause drowsiness and dizziness.
Eye Contact	May cause slight irritation.
Skin Contact	Prolonged or repeated contact may dry skin and cause irritation
Ingestion	Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Stearic acid	-	5 g/kg (Rabbit)	-
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-	= 4190 mg/kg (Rat)		
Hexylene glycol	= 3692 mg/kg (Rat)	12,3000 mg/kg (Rabbit)	> 310 mg/m ³ (Rat) 1 h
Alumina	> 5000 mg/kg (Rat)		
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Triethanolamine	= 4190 mg/kg (Rat)	> 16 mL/kg (Rat) > 2000 mg/kg (Rabbit)	
Tall oil fatty acids	= 7600 mg/kg (Rat)		

Chronic Toxicity

Chronic Toxicity

Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

Chemical Name	ACGIH	IARC	NTP	OSHA
Triethanolamine		Group 3		

Target Organ Effects

Central nervous system (CNS). Eyes. Respiratory system. Skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Do not allow material to contaminate ground water system.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light		LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 45 mg/L flow-through (Pimephales promelas)		LC50 96 h: = 4720 mg/L (Daphnia magna)
Triethanolamine	EC50 96 h: = 169 mg/L (Desmodesmus subspicatus) EC50 72 h: = 216 mg/L (Desmodesmus subspicatus)	LC50 96 h: 10600-13000 mg/L flow-through (Pimephales promelas) LC50 96 h: 450-1000 mg/L static (Lepomis macrochirus) LC50 96 h: > 1000 mg/L static (Pimephales promelas)	EC50 > 10000 mg/L 30 min	EC50 24 h: = 1386 mg/L (Daphnia magna)
Tall oil fatty acids	EC50 72 h: >= 1000 mg/L (Pseudokirchneriella subcapitata)			
Hexylene glycol		LC50 96 h: 10500-11000 mg/L flow-through (Pimephales promelas) LC50 96 h: = 10000 mg/L static (Lepomis macrochirus) LC50 96 h: = 10700 mg/L static (Pimephales promelas) LC50 96 h: = 8690 mg/L flow-through (Pimephales promelas)	EC50 = 3038 mg/L 5 min	EC50 48 h: 2700 - 3700 mg/L (Daphnia magna)

Chemical Name	Log Pow
Triethanolamine	-2.53
Tall oil fatty acids	5.98
Hexylene glycol	0.13986

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

California Hazardous Waste Codes 331

14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
EINECS	Complies
ELINCS	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Solvent naphtha (petroleum), medium aliphatic	X				
Alumina	X	X	X		X
Triethanolamine	X	X	X		X
Hexylene glycol	X	X	X		X

International Regulations**Mexico - Grade**

Slight risk, Grade 1

Chemical Name	Carcinogen Status	Exposure Limits
Hexylene glycol		Mexico: Ceiling= 125 mg/m ³ Mexico: Ceiling= 25 ppm
Alumina		Mexico: TWA= 10 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials

**16. OTHER INFORMATION****Prepared By**

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date

03-Apr-2007

Revision Date

11-Mar-2011

Revision Note

Product Code change.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet